

SAFETY DATA SHEET FOR COATINGS, RESINS, AND RELATED MATERIALS

NG BLANKS SINCE 1969 **SECTION I – Chemical Product and Company Identification**

Product name:

Gutta Resist – 781 Black

Catalog Code:

JAC1781, JAC2781 and JAC3781

Supplier:

Rupert, Gibbon & Spider, Inc.

1147 Healdsburg Avenue Healdsburg, CA 95448 USA

Product class:

Solvent-based rubber adhesive

Material uses:

Resin used for silk – painting arts

Information

telephone number:

800-442-0455

Emergency

telephone number:

(800) 424-9300 Chemtrec

(703) 527-3887 Outside the United States

SECTION II – Hazards identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product:

Flammable Liquids

Skin Corr. /Irrit. 2 Skin irritation

Eye Dam. /Irrit.

2A

serious eye damage/eye irritation

Reproductive

Toxicity

STOT SE

Central nervous system

STOT RE

Central nervous system, Peripheral nervous system

Aspiration hazard

Label elements

Pictogram:









Signal Word: Danger

Hazard Statement:

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs (Auditory system, Eyes) through prolonged or repeated exposure if inhaled.

Precautionary Statements (Prevention):

- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/gas/mist/vapours.
- P264 Wash with plenty of water and soap thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

Precautionary Statements (Response):

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P331 Do NOT induce vomiting.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.
- P370 + P378 In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

Precautionary Statements (Storage):

P233 Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified:

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Potential health effects:

Carcinogenicity:

For Component: VMP Naphtha

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

For Component: Isopropanol

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by ACGIH.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by OSHA

SECTION III – Composition/Information on Ingredients

| SECTION III – Composition/Information on Ingredients | | | | | |
|--|-------|-----------|----------|------------|--|
| Ingredients | % | ACGTH-TLV | OSHA-PEL | CAS No. | |
| Aliphatic | 76.5 | 300 ppm | 300 ppm | 64742-89-8 | |
| Petroleum | | | | | |
| Distilutes | | | | | |
| Isopropyl Alcohol | 1.8 | 400 ppm | 400 ppm | 67-63-0 | |
| Propylene Glycol | 3-3.5 | | | 108-65-6 | |
| Mono Methyl | | | | | |
| Ether | | | | S H | |
| Carbon Black | 1.5-2 | | | 1333-86-4 | |
| Talc | .15 | | | 14807-96-6 | |
| Ethyl Benzene | .011 | | 2000 | 100-41-4 | |

SECTION IV – FIRST AID MEASURES

Eye Contact:

In case of contact, flush eyes with plenty of lukewarm water. Use fingers to ensure that the eyelids are separated and that the eye is being irrigated. Get medical attention if irritation develops.

Skin Contact:

In case of skin contact, wash affected areas with soap and water. Immediately remove contaminated clothing and shoes. Call physician if irritation develops or persists. Thoroughly clean shoes before reuse. Wash contaminated clothing before reuse.

Inhalation:

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Ingestion:

If ingested, do not induce vomiting unless directed to do so by medical personnel. Get medical attention.

SECTION V – FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Use water, foam or dry chemicals.

Special Fire Fighting Procedures:

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes. Toxic and irritating gases/fumes may be given off during burning or thermal decomposition. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture.

Unusual Fire/Explosion Hazards:

Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback. Vapors or fumes may foam explosive mixture with air.

Hazardous Thermal Decomposition Products:

In case of fire, may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, (dense) black smoke, aldehydes, organic acids, nitrogen oxides, ammonia, amines.

SECTION VI – ACCIDENTAL RELEASE MEASURES

Spill and Leak Procedures:

Contain spill. If spilled in an enclosed area ventilate. Wear proper personal protective clothing and equipment. Do not flush liquid in public sewer, water systems or surface waters. Recover as much as possible and absorb remainder with inert material. Place into labeled containers and store in safe locations for proper disposal. Wash spilled areas with soap and water.

SECTION VII - HANDLING AND STORAGE

Storage Temperature: Minimum:

5°C (41°F)

Maximum 40°C (104°F)

Handling:

Avoid eye contact, repeated or prolonged skin contact or inhalation of aerosol, mist or vapors. Wash thoroughly after handling. Use in well ventilated areas.

Storage:

Keep containers closed when not in use. Do not store in open, unlabeled or mislabeled containers. Product is not reactive or degraded by moisture, however protect from moisture contamination for performance purposes.

SECTION VIII – EXPOSURECONTROLS/ PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH-TWA ACGIH-STEL OSHA-TWA OSHA-STEL Page **5** of **15**

Isopropanol 200 ppm 400 ppm 500 ppm 500 ppm

Distillates, pet, lt dist hydrotreat Process, low-boil AND/OR Naphtha (pet), hydrotreated lt AND/OR Solvent

Naphtha (pet), it aliph. N/E N/E 500 ppm N/E

Engineering Controls:

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal Protection

Eyes:

Chemical safety goggles or safety glasses with side-shields. Chemical safety goggles/safety glasses

Skin:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory:

Use a properly fitted, air-purifying or air fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and safe working limits of the known respirator.

Hand:

Permeation resistant gloves, Butyl rubber gloves, Nitrile rubber gloves, Neoprene gloves.

Additional Protective Measures:

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Emergency showers and eye wash stations should be available. Store separate from food products.

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid Appearance: Paste

Odor: Hydrocarbon-like

Solubility in Water: N/A **PH:** N/A

Flash Point:

54° F. **Boiling**

Range:

180°F.

Evaporation Rate:

Slower than Ether

Vapor Density:

Heavier than Air

% Volatile by Weight: Specific Gravity:

86.0 % 0.79

Lb. VOC/Gal. Coating:

5.56

VOC g/l:

666.23

SECTION X - STABILITY AND REACTIVITY

Stability:

This product is stable under normal storage and use conditions.

Hazardous Polymerization:

Will not occur.

Incompatibility:

Strong oxidizing agents, excessive heat.

Hazardous Decomposition Products:

Decomposition of the dry solids may generate irritating vapors, CO2, CO.

SECTION XI – TOXICOLOGICAL INFORMATION

Toxicity Data for XS-4139-N

Toxicity Note:

No data available for this product.

Toxicity Data for Isopropanol

Component:

67-63-0:

Acute Oral Toxicity:

LD50 (rat):

5,045 mg/kg

Acute Inhalation:

LC50 (rat):

16000 ppm

Acute Dermal Toxicity:

LD50 (rabbit): 12,800 mg/kg

Skin Irritation:

Component:

<u>67-63-0:</u>

Species: Rabbit

Result: Mild skin irritation.

Eye Irritant: Component: 67-63-0:

Species: rabbit

Result: Irritating to eyes

Respiratory or Skin Sensitization:

Component: 67-63-0:

No data available.

Germ Cell Mutagenicity:

Component:

67-63-0: Genetic Toxicity in Vitro:

Test Type: Ames test

THE BLANKS SINCE. Test species: Salmonella typhimurium

Result: negative

Genotoxicity in vivo:

Test Type: In vivo micronucleus test

Test species: mouse

Method: OECD Test Guideline 474

Result: negative

Test Type: Dominant lethal assay

Test species: mouse (male)

Application Route: Inhalation (vapour) Exposure time: 6 h/d, 5 d/wk for 8 wks

Dose: 0, 100, 400 ppm

Result: negative

Germ cell mutagenicity-

Assessment:

Did not show mutagenic effects in animal experiments.

Component:

Carcinogenicity:

67-63-0:

Species: rat

NOAEL: 5,000 ppm

Method: OECD Test Guideline 451

Carcinogenicity-Assessment: Not classified as a human carcinogen.

Toxicity to Reproduction/Fertility:

Component:

67-63-0:

Reproductive toxicity-

Assessment:

Animal testing did not show any effects on fertility. Did not show

teratogenic effects in animal experiments.

STOT – **single exposure (Isopropanol)**

Component:

<u>67-63-0:</u>

| Exposure routes: | Target Organs: | Assessment: | Remarks: |
|-------------------------|-----------------|------------------------|----------|
| Inhalation | Central nervous | May cause drowsiness | |
| | system | or dizziness. The | |
| | ~~. | substance or mixture | |
| | | is classified as | |
| | | specific target organ | |
| | | toxicant, single | |
| | S. S. | exposure, category 3 | |
| | | with narcotic effects. | |

STOT – repeated exposure (Isopropanol)

Component:

<u>67-63-0:</u>

No data available.

Toxicity Data for VMP Naphtha:

Component:

68410-97-9/64742-49-0/64742-89-8:

Acute Oral Toxicity:

LD50: >5,000 mg/kg

Species: (rat, male and female) Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral toxicity.

Acute inhalation toxicity:

Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity:

LD50: >2,000 mg/kg

Species: (rabbit, male and female) Method: OECD Test Guideline 402

rmal toxicity. Assessment: The substance or mixture has no acute dermal toxicity.

Skin irritation:

Component:

68410-97-9/64742-49-0/64742-89-8:

Species: Rabbit Exposure time: 4 h Result: Irritating to skin.

Remarks: May cause skin irritation in susceptible persons.

Eve irritation: Component:

68410-97-9/64742-49-0/64742-89-8

Species: Rabbit

Result: Irritating to eyes.

Respiratory or Skin Sensitization:

Component:

68410-97-9/64742-49-0/64742-89-8:

Test Type: Buehler Test Species: Guinea pig

Result: Did not cause sensitization on laboratory animals.

Germ Cell Mutagenicity:

Component:

68410-97-9/64742-49-0/64742-89-8:

Germ cell mutagenicity-

Assessment: Mutagenicity classification not possible from current data.

Carcinogenicity:

Component:

68410-97-9/64742-49-0/64742-89-8:

Carcinogenicity-Assessment: Carcinogenicity classification not possible from current data.

Toxicity to Reproduction/Fertility:

Component:

68410-97-9/64742-49-0/64742-89-8:

Reproductive toxicity-

Assessment:

Some evidence of adverse effects on sexual function and fertility, __certility

based on animal experiments.

STOT – single exposure (VMP Naphtha)

Component:

68410-97-9/64742-49-0/64742-89-8:

| Exposure routes: | Target Organs: | Assessment: | Remarks: |
|-------------------------|-----------------|------------------------|----------|
| Inhalation | Central nervous | May cause drowsiness | |
| | system | or dizziness. The | |
| | | substance or mixture | |
| | | is classified as | |
| | | specific target organ | |
| | ~ ~ ~ | toxicant, single | |
| | | exposure, category 3 | |
| | | with narcotic effects. | |

STOT – repeated exposure (VMP Naphtha)

Component:

68410-97-9/64742-49-0/64742

| Exposure routes: | Target Organs: | Assessment: | Remarks: |
|-------------------------|--------------------|-----------------------|----------|
| | Central nervous | The substance or | |
| July 1 | system, Peripheral | mixture is classified | |
| The state of | nervous system | as specific target | |
| | | organ toxicant, | |
| | | repeated exposure, | |
| | | category 2. | |

Repeated dose Toxicity:

Component:

68410-97-9/64742-49-0/64742-89-8:

Species: Rat, male and female

NOAEL: 1402

Application Route: inhalation (vapour)

Test atmosphere: vapour Exposure time: 13

Number of exposures: 6 hours/day, 5 day

Dose: 322, 1402, 9869 mg/m3

GLP: yes

Target Organs: Kidney

Symptoms: Nasal and ocular discharge

Aspiration toxicity:

Component:

<u>68410-97-9/64742-49-0/64742-89-8:</u>

May be fatal if swallowed and enters airways.

SECTION XII - ECOLOGICAL INFORMATION

S SINCE 1969

Ecological Data for XS-4139-N

Additional Ecotoxicological Remarks:

No data available for this product.

Ecological Data for VMP Naphtha:

Ecotoxicity: Component:

68410-97-9/64742-49-0/64742-89-8:

Toxicity to fish; LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l

Exposure time: 96 h Test Type: semi-static test

Toxicity to daphnia and

other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 4.5 mg/l

Exposure time: 48 h

Test Type: Immobilization Analytical monitoring: yes

Toxicity to algae: EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7 mg/l

Exposure time: 96 h Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity: Toxic to aquatic life.

Chronic aquatic toxicity: Toxic to aquatic life with long lasting effects.

Page 12 of 15

Persistance and degradability:

Component:

68410-97-9/64742-49-0/64742-89-8:

Biodegradability: Concentration: 49.2 mg/l

Result: Readily biodegradable

Biodegradation: 77 % Testing period: 2 d Exposure time: 28 d

Mobility in soil:

Component:

68410-97-9/64742-49-0/64742-89-8:

No data available

Ecological Data for Isopropanol:

Ecotoxicity Component: 67-63-0:

Toxicity to fish:

id m. LC50: (Pimephales promelas (fathead minnow)):> 1,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and

other aquatic invertebrates:

LC50: > 100 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

Toxicity to algae:

Remarks: No data available.

Mobility in soil:

Component:

67-63-0;

No data available

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose of in accordance with Federal, State and Local regulations.

SECTION XIV – TRANSPORTATION INFORMATION

Land transport (DOT):

UN Number: 1133 UN Packing Group: II UN Class: III

DOT Hazard Class: Flammable Liquid

Sea transport (IMDG):

UN Number: 1133 UN Packing Group: II UN Class: III

Air transport (ICAO/IATA):

UN Number: 1133 UN Packing Group: II UN Class: III

O/IATA): 1133 II III SECTION XV – REGULATORY INFORMATION

SARA Title III Section 313:

This product contains the following substance(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (40 CFR 372).

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA Title III 312 Hazard Category (40 CFR 311/312):

Acute Health: Yes Release of Pressure: No Chronic Health: Yes Reactive: No

Fire: Yes

US Federal Regulations (TSCA):

This product is listed on the U.S. Toxic Substance Control Act inventory of chemicals or is otherwise compliant with TSCA regulations.

SECTION XVI – OTHER INFORMATION

HMIS Rating:

Health: 2

Flammability: 3 Reactivity: 0 PPE: B

Date of Printing: 11/2/2016

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS PRODUCT OR INFORMATION, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. The information and product are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use thereof.